General Information

General Information		
Design	Bridge-type CMM with stationary machine table and lateral bridge drive.	
Operating Mode	Motorized / CNC	
Laser / Part Indexing	Fixed / Renishaw PH10M	
Length Measuring System	Reflected light length measuring system, photoelectric 0.2 µm (0.000008 in) resolution.	
Special Features	Ceramic crossbeam and spindle. Pneumatically counterbalanced Z axis. Preloaded high performance air bearings with wrap around guideways in all axes. Passive anti-vibration system.	
Drive System	High-performance servo drives. Electronic monitoring of position control in all axes.	
Controller	Type: C99L (CNC 3-axis vectorial control) Cooling System: Integrated Fan	
Accessories	Standard control panel: 2 joysticks with progressive characteristics for manual control.	
Power Requirements	100-240 V VAC ~ (+10%, -15%); 50-60 Hz (±3.5%), Power consumption: max. 750 VA	
Environmental Requirements	+17° to +35°C (63°-95°F)	
Compressed Air Supply	Supply pressure 6 - 10 bar, pre-cleaned. Maximum consumption: 25 l/min at 5 bar pressure. Air quality according to ISO 8573 part 1: class 4.	
Axes	X, Y, Z, optional rotary stage	
Bearing System	Air bearings	
Measuring Table	Black granite	
Measuring System	Optical linear transducers	
Warranty	1-year warranty (hardware, software, parts, labor, workmanship)	

Included with System

meradea with system		
XLP 250, 500, or 1000		
Surveyor Scan Control Software		
High-end Windows based PC and monitor		
Adjustable mounts allow for 2 axes of rotation		
Specially designed artifact for validating system accuracy. Includes CMM inspection report and Qualify inspection template		

System Options

Rotary Stage	ADRS 150 high accuracy rotary stage		
Renishaw PH10	2-axis Renishaw PH10M		
7th Axis	Laser Design automated flip fixture		
Manual Fixtures	Manual flip fixture and extra frames		
Reverse Engineering Software	Geomagic Design X, Polyworks/ Inspector		
Inspection Software	Geomagic Control X, Polyworks/ Inspector		

Measuring Range (MM)

CMM Sizes	Measuring range in mm (in)		
	X axis	Y axis	Z axis
5/5/5	500 (19.7)	500 (19.7)	500 (19.7)
7/7/6	700	700 (27.6)	•
7/10/6	(27.6)	1000 (39.4)	600 (23.6)
10/12/6	1000	1200 (47.2)	(23.0)
10/16/6	(39.4)	1600 (63.0)	-

Volumetric Accuracy CMM Base-ISO 10360-2

Model	Renishaw TP200 Probe Standard Accuracy	
	MPE _E MPE _F	
500 & 700	2.4 + L/250	2.4
1000	2.7 + L/250	2.7

Laser Design also offers system upgrades for the ZS-Series for traditional CMM functionality. For information on adding a wide variety of Renishaw sensors and touch probing capability to your machine, please contact your Laser Design Sales representative.

Contact Laser Design today for more information 952.884.9648 | info@laserdesign.com | www.laserdesign.com

Copyright © 2017. Laser Design Inc. All rights reserved. Specifications subject to change without notice. Rev A

Surveyor® ZS-Series

High Precision Design and Accuracy



Surveyor® ZS-Series

3D Laser Scanning Systems

The ZS-Series integrated with Laser Design's laser scanning probes set a new standard for precision and ease of use in 3D measurement. Systems are available in many sizes to accommodate different types of parts and applications. The Surveyor ZS-Series systems are CE rated, making them an ideal choice for customers worldwide. Operators can quickly and easily scan simple prismatic shapes and geometry, free-form surfaces, or complex-shaped objects for inspection, analysis, or reverse engineering applications.



High Precision Design and Accuracy

The ZS-Series scanning system offers excellent stability and rigidity through passive anti-vibration technology while scanning at maximum speed and acceleration. The bridge-type CMM has a ceramic crossbeam and spindle with a pneumatically counterbalanced Z axis. The preloaded high-performance air bearings with wrap around guideways in all axes mean support from all four sides, guaranteeing superior measuring capabilities. Ceramic guideway elements ensure corrosion resistance, hardness and wear resistance, electrical resistance, temperature resistance, and a low friction coefficient. The integrated C99L controller supplies smooth, accurate, high-speed 3-axis movement for all measuring applications.

Dynamics

		500 and 700	1000
Travel Speed	Motorized Axes:	0 to 70 mm/s (2.8 in/s)	0 to 70 mm/s (2.8 in/s)
	CNC: X Axis: Y Axis:	Max. 200 mm/s (7.9 in/s)	Max. 175 mm/s (6.9 in/s)
	Z Axis:	Max. 346 mm/s (13.6 in/s)	Max. 303 mm/s (11.9 in/s)
Acceleration	Vector:	Max. 500 mm/s ² (19.7 in/s ²)	Max. 500 mm/s² (19.7 in/s²)
	Axes:	Max. 866 mm/s ² (34.1 in/s ²)	Max. 866 mm/s² (34.1 in/s²)

Industry Best for Laser Line Scanning Technology

Laser Design's XLP Laser Scanning Probes are able to scan diverse surface materials without any special coatings. They are up to 50% more accurate, up to 70% faster scan rate, and up to 30% higher resolution.


The XLP comes in three models based on the size and detail on the objects to be scanned. Parts such as plastics, metal, rubber, cast, molded, forged, machined, or extruded components, as well as tooling dies, or molds, are all typically measured items.





Intuitive, Easy-to-Use Software

Surveyor Scan Control (SSC) software has a simple Windows interface that makes laser scanning easy to use, with scanning wizards that automate most day-to-day tasks with detailed accuracy reporting that helps you know the accuracy of your machine before you start collecting data. Automated scanning gives you control up to 7 axes of motion for complete coverage from a single program.



SSC provides optimization for part specularity, data density control, and filtering as well as macro programming capabilities for automating repetitive applications and eliminating operator involvement.

Software and Applications

Laser Design offers the industry's leading data processing software packages including: Geomagic, PolyWorks, and Verisurf for reverse engineering and inspection applications. Our turnkey 3D scanning system solutions include application-specific software for output of:

- Inspection / Verification Reports
- 3D Color Error Maps
- CAD Models (parametric, non-parametric, parasolids, surface NURBS, etc.)
- STL Meshes

- Point Clouds
- Isolated key design features
- Many other analytic or geometric formats

Reverse Engineering and Inspection

The Surveyor ZS-Series with the XLP scanning probe captures the highest resolution point cloud providing the best reference to create 3D CAD surface models or low-cost production of STL files for rapid prototyping.

Revolutionize your inspection process by implementing complete part characterization / analysis based upon millions of coordinates defining the part's shape rather than the few hundred coordinates of touch probe measuring. Any part geometry out of compliance with the CAD model is immediately revealed. Locations of critical datums and full GD&T measurements are quickly displayed and included in easy-to-read graphic reports.

Laser scan data can be combined with touch probe data in the same inspection report. Full dimensional spreadsheets can be output to conventional SPC as desired. Once an inspection report is created, it can be automated for second part output without operator involvement, making multiple part inspections much faster and more thorough than ever before.

